

Specification Sheet

810 series Pump Heads only

Specification Sheet (last updated May 2019)



The ever popular WPL 810 series peristaltic pumps are available in a range of AC and DC motor options and various tube size combinations delivering flow rates as high as 987 ml/min. They are self priming up to 29 ft. (8.8m), can be run dry continuously, and are non-siphoning.

The easiest way to place an order or check prices is via our online shop at http://www.williamson-shop.co.uk but please contact us for any requirements not listed or to place an order over the phone.

Model No	Series	ml/rev*	Rollers	Tube id/material	
810.PH.187/2	810 series pumphead	2	2	4.8	55 food sant
810.PH.187/3	810 series pumphead	1.75	3	4.8	55 food sant
810.PH.250/2	810 series pumphead	3.5	2	6.4	55 food sant
810.PH.250/3	810 series pumphead	3	3	6.4	55 food sant
811.PH.187/2	810 series pumphead	2	2	4.8	silicone.
811.PH.187/3	810 series pumphead	1.75	3	4.8	silicone.
811.PH.250/2	810 series pumphead	3.5	2	6.4	silicone.
811.PH.250/3	810 series pumphead	3	3	6.4	silicone.

^{*} To calculate flow per minute, multiply ml/rev by RPM of motor gearbox being used

NB:- flow figures should be used only as an estimate. Customers should run their own tests to establish pump suitability

Williamson Manufacturing Company Ltd

Unit 5, Lady Bee Industrial Estate, Albion Street, Southwick, West Sussex, BN42 4EP,UK. Tel +44(0)1273 857752 E Mail:- sales@williamsonpumps.co.uk Web www.wmcpumps.com